

1. CHEMICAL PRODUCT AND COMPANY DESCRIPTION

AQUATROLS CORP
1273 IMPERIAL WAY

PAULSBORO, NJ 08066 USA

Emergency Phone Numbers: For chemical emergency spill, leak, fire, exposure or accident, call CHEMTREC
Day or Night: Domestic North America 800-424-9300. International call 703-527-3887 (collect calls accepted).

For Product Information: 800-257-7797 or www.aquatrols.com

Chemical Name or Synonym: Non-ionic surfactant, wetting agent.

C.A.S. Number: Proprietary

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Reg. Number	Weight (%)	**Exposure Limits**	
			OSHA/PEL	ACGIH/TLV
Non-ionic surfactant	Proprietary*	> 99.5	Not established	Not established
Water	7732-18-5	< 0.5	N/A	N/A
Dioxane	123-91-1	< 0.001		90 mg/m ³
Ethylene Oxide	75-21-8	< 0.001		1.8 mg/ m ³
Propylene Oxide	75-56-9	< 0.001		48 mg/ m ³

* Trade secret as allowed by 29 CFR 1901.1200-48

3. HAZARDS IDENTIFICATION**A. Emergency Overview:**

Physical Appearance and Odor: Clear to hazy viscous liquid, slight odor.

Warning Statements: CAUTION: May cause irritation.

B. Potential Health Effects:

Primary Route of Entry: Routes of entry for liquids include eye and skin contact, inhalation and ingestion.

Effects of Overexposure:

Acute Eye: Slightly irritating. May cause excessive watering, redness, and/or irritation.

Acute Skin: Low acute dermal toxicity. Slightly irritating. May cause redness.

Acute Inhalation: Inhalation is not likely. Mists may cause upper respiratory tract irritation.

Acute Ingestion: Overexposure may cause gastrointestinal irritation, diarrhea, nausea, and vomiting.

Chronic Effects: This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogens.

4. FIRST AID MEASURES

EYE CONTACT: DO NOT RUB EYES. Immediately flush eyes with large amounts of water for 15 minutes lifting the lower and upper lids. Seek medical attention if necessary.

SKIN CONTACT: Remove contaminated clothing and immediately wash affected area with large amounts of water for at least 5 minutes. If irritation or redness persists, seek medical attention as needed.

IF SWALLOWED: If victim is conscious and able to swallow, quickly give milk or water to dilute. Do not give sodium bicarbonate, vinegar, or fruit juices. Seek medical attention if necessary. Induce vomiting only upon advice from a physician.

INHALATION: Move individual to fresh air and check to assure adequate respiration. Seek medical attention if necessary.

Medical Conditions Possibly Aggravated by Exposure: Skin contact may aggravate existing skin conditions.

Notes to Physician: All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Treat symptomatically. No specific antidote is available.

5. FIRE FIGHTING MEASURES**FIRE HAZARD DATA:****Flash Point:** > 93°C (200°F). Flammability class: WILL BURN. **Method Used:** Pensky-Martens Closed Cup**Flammability Limits (vol/vol%): Lower:** Not established **Upper:** Not established**Extinguishing Media:**

Recommended:

Small fires – dry chemical, carbon dioxide

Large fires – alcohol foam, universal foam, water spray

Not Recommended:

Water jet (frothing possible)

Special Fire Fighting Procedures: Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing.**Unusual Fire and Explosion Hazards:** Product will burn under fire conditions.**Hazardous Decomposition Materials (Under Fire Conditions):** Oxides of carbon.**6. ACCIDENTAL RELEASE MEASURES****Containment of Spill:** Follow procedure described below.**Cleanup and Disposal of Spill:** Absorb with an inert absorbent. Sweep up and place in an appropriate closed container. Clean up residual material by washing area with water. Collect washings for disposal.**Environmental and Regulatory Reporting:** Do not flush to drain. Spills may be reportable to the National Response Center (800-424-8802) and to state and/or local agencies.**7. HANDLING AND STORAGE****Minimum/Maximum Storage Temperature:** 15 to 49°C (59 to 120°F)**Handling:** Avoid breathing vapors and mists. Avoid direct or prolonged contact with skin and eyes. Ethylene oxide may collect in container head space. Although concentrations are expected to remain below established exposure limits, provide adequate ventilation when accessing or working with open containers and tanks.**Storage:** Store in tightly closed containers. Store in an area that is dry, well-ventilated, away from ignition sources, and away from incompatible materials (see Section 10. Stability and Reactivity).**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Introductory Remarks:** These recommendations provide general guidance for handling this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. While developing safe handling procedures, do not overlook the need to clean equipment and piping systems for maintenance and repairs. Waste resulting from these procedures should be handled in accordance with Section 13: Disposal Considerations.

Assistance with selection, use and maintenance of worker protection equipment is generally available from equipment manufacturers

Exposure Guidelines: No exposure limits were found for this product or any of its ingredients.**Engineering Controls:** When potential for exposure exists, provide adequate general area dilution/exhaust ventilation.**Respiratory Protection:** When respirators are required, use a suitable NIOSH/MSHA approved equipment based on actual or potential airborne concentrations and in accordance with the appropriate regulatory standards and/or industrial recommendations. Under normal conditions with adequate ventilation, no protection is necessary.**Eye/Face Protection:** Appropriate ANSI Z87 approved equipment should be selected for the particular use intended for this material. An available eyewash station is recommended.**Skin Protection:** Skin contact should be minimized through use of appropriate long-sleeved clothing (i.e., shirts and pants). Consideration must be given both to durability as well as permeation resistance. USDA accepted Nitrile (CFR-20) or neoprene rubber (CFR-21) gloves are recommended

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Chemical additions, processing or otherwise altering this material may make the waste management information in this MSDS incomplete, inaccurate or inappropriate. Please be advised that state and local requirements for waste disposal may be more restrictive or different from federal laws and regulations. Consult state and local regulations regarding the proper disposal of this material.

14. TRANSPORTATION INFORMATION

Transportation Status: The listed Transportation Classification does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors.

US Department of Transportation Shipping Name: Not Regulated

15. REGULATORY INFORMATION**Inventory Status:**

Inventory	Status
UNITED STATES (TSCA)	Y
CANADA (DSL)	Y
EUROPE (EINECS/ELINCS)	P
AUSTRALIA (AICS)	Y
JAPAN (MITI)	Y
SOUTH KOREA (KECL)	Y

Y: All ingredients are on the inventory.

E: All ingredients are on the inventory or exempt from listing.

P: One or more ingredients fall under the polymer exemption or are on the no longer polymer list. All other ingredients are on the inventory or exempt from listing.

N: Not determined or one or more ingredients are not on the inventory and are not exempt from listing.

FEDERAL REGULATIONS:

Inventory Issues: All functional components of this product are listed on the TSCA inventory.

SARA Title III Hazard Classes:

Fire Hazard	NO
Reactive Hazard	NO
Release of Pressure	NO
Acute Health Hazard	NO
Chronic Health Hazard	NO

OTHER FEDERAL REGULATIONS:

FDA Status: N/A

FIFRA Status: N/A

STATE REGULATIONS: This product contains the following components that are regulated under California Proposition 65:

Ingredient	Cancer List	Reprod. List	No Sig. Risk Lvl. (ug/day)	RPI
Dioxane	Y	N	30	ND
Ethylene Oxide	Y	Y	2	ND
Propylene Oxide	Y	N	3	ND

16. OTHER INFORMATION**National Fire Protection Association Hazard Ratings – NFPA(R):**

- 1 Health Hazard Rating -- Slight
- 1 Flammability Rating -- Slight
- 0 Reactivity Rating -- Minimal



SIXTEEN/90

Material Safety Data Sheet Date Prepared: March 1, 2005

Supersedes Date: July 12, 2004

National Paint and Coating Hazardous Materials Identification System - HMIS(R):

- 1 Health Hazard Rating -- Slight
- 1 Flammability Rating -- Slight
- 0 Reactivity Rating -- Minimal

Reason for Revisions: Company location change. This MSDS replaces July 12, 2004, MSDS.

Key Legend Information

ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety and Health Administration
TLV	Threshold Limit Value
PEL	Permissible Exposure Limit
TWA	Time Weighted Average
STEL	Short-Term Exposure Limit
NTP	National Toxicology Program
IARC	International Agency for Research on Cancer
ND	Not determined

Disclaimer:

While the information and recommendations set forth herein are believed to be accurate, we make no warranty with respect hereto and disclaim all liability from reliance thereon.

End of MSDS Document